



## LCS-8539TXR1

10/100 Mbit/s  
Cardbus Card



The LCS-8539TXR1 10/100Mbit/s CardBus Card connects your Notebook to wired LAN structures. The Adapter is easy to install and configure. The card delivers data rates from 10 up to 100 Mbit/s, both with Full/Half-Duplex and Full-Duplex Flow Control. The card supports ACPI and Wake-up Function with Magic Packets. The Adapter provides Drivers for all common operating systems.

### Features:

- ◆ Compliant to IEEE 802.3u, 802.3, 802.3x Specifications.
- ◆ 10/100Mbit/s
- ◆ CardBus 32-Bit Interface
- ◆ Supports ACPI
- ◆ Supports Wake-up Functions with Magic Packets
- ◆ Massive integrated RJ-45 Port
- ◆ Supported OS:
  - ODI drivers: Novell Netware 3.x, 4.x, 5
  - Packet drivers: FTP PC/TCP, NCSA TCP/EP
  - NDIS 2.0 drivers: Microsoft LAN manager, Windows for Workgroups
  - NDIS 3.0 drivers: WFW 3.11, Windows 95, Windows NT3.51
  - NDIS 4.0 drivers: Windows NT4.0
  - NDIS 5.0 drivers: Windows 98/98SE, Windows ME, Windows 2000, Windows XP
  - Linux drivers: Redhat, TurboLinux, FreeBSD

### Specifications:

<b>Standards:</b>	IEEE 802.u, IEEE 802.3u, IEEE802.3,
<b>Bus:</b>	PCMCIA Type II slot, 32-Bit
<b>Powersafe Modi:</b>	ACPI and CardBus Power Management
<b>Port:</b>	1* RJ-45
<b>Data rate:</b>	10/100Mbit/s with Half- and Full-Duplex
<b>Fifo:</b>	2K for send/receive
<b>Chip:</b>	Realtek
<b>OS:</b>	Windows 95/98x/NT4.0/ME/2000/XP, RedHat, TurboLinux, FreeBSD Novell NetWare3.x, 4.x, 5
<b>Certificates:</b>	FCC, CE
<b>Power:</b>	Consumption 3.3V
<b>Dimensions:</b>	116mm x 54mm (L x W), 40g
<b>Workaround:</b>	Temperature 0° ~ 65° C
<b>Box contains:</b>	CardBus Card, Driver CD, Manual
<b>EAN:</b>	4 016621 005498