



LCS-IR2114-B

Internetrouter + 4-Port Switch



Longshines IR2114-B is a full-featured broadband router that establishes with connection to local area network or individual PC with build-in 4-port Switch. IR2114-B uses advanced WavePlus broadband router solution provides complete set of industry standard features for high-speed Internet access. IR2114-B offers easy installation and cost-effective connection for corporate, SOHO and residential users.

Longshines IR2114-B broadband router provides maximum transfer rate up to 90Mbps from WAN to LAN, 100 Mbps from LAN to LAN. IR2114-B provides password protected configuration function guarantees the best security on CO settings. No need user intervention. Included DHCP server assigns IP addresses to all workstations on your LAN.

All Longshine products are made in ISO9001 approved factory. IR2114-B Broadband Router complies with FCC part 15 regulations and CE approval.

Features:

- ◆ Maximum transfer rate up to 90Mbps from WAN to LAN, 100Mbps LAN to LAN
- ◆ Friendly GUI Configuration and Management software
- ◆ Supports IEEE 802.3 full duplex flow control
- ◆ Built-in DHCP server automatically assigns IP address to all workstations on your LAN.
- ◆ Supports MAC filter, Client filter, URL and IP filter blocking and Hacker pattern detection
- ◆ Supports ALGs (Microsoft NetMeeting, MSN Messenger, Windows Media Player, DirectX 8.0, PPTP pass through, IPSec pass through, FTP, ICMP, SMTP, POP3, DNS, Telnet, HTTP, HTTPS, H.323, SIP, Real Audio, CuSeeMe, AOL, and Games)

Specifications:

Data Transfer Rates	WAN to LAN : up to 90Mbps, LAN to LAN : 100Mbps
Standard	IEEE 802.3 10Base-T, IEEE 802.3u 100Base-Tx, RFC 2516 (PPP over Ethernet)
Bridging	IEEE 802.1x
Routing	Static Routing, RIP version 1 (RFC 1058) and version 2 (RFC 1723), NAT (Network Address Translation), NAT (Network Address and Port Translation), DHCP (Dynamic Host Configuration Protocol) Server/Client
Security & Management	Clone MAC, Supports DDNS, Configuration of NAT/NAPT, Supports Virtual Server and Virtual DMZ, Provides MAC filter, Client filter, and URL/IP filter, WAN, LAN, DMZ and AP statistics, Restore to Factory Default, System Log, UPnP, ALG and Help, Software Upgrade through Web, Firewall
Interface	LAN x 4, WAN x 1
LED Indicators	POWER, STATUS, WAN, LAN x 4
Power	AC 9V, 1A
Dimensions (app)	125mm (length) x 85mm (width) x 25mm (height)
Net Weight (app)	125g
Operating Temperature	0°C ~ 40°C (32°F ~ 104°F)
Humidity	5 % ~ 95 % (non-condensing)
Storage Temperature	0°C ~ 70°C
Regulations	FCC Part 15 class B, CE
EAN	4016621101305