


LCS-M13Qxx

13.3" Outdoor Monochrome EPD Signage



PRELIMINARY

Outdoor 13.3" Electronic Paper Monochrome Display for Digital Signage Remote Application.

Features:

- ◆ Sunlight Readable
- ◆ Ultra Wide Viewing Angle
- ◆ Wide Operation Temperature Range -15°C ~ 65°C
- ◆ IK07 Compatible Anti Vandalic Tempered AR Glass
- ◆ IP66 Compatible Moisture and Dust Protection
- ◆ UV Cutting and Anti Reflection
- ◆ Low Power Consumption
- ◆ 4G Connection & Ethernet
- ◆ Optional Bluetooth/WIFI
- ◆ Anti Theft Fixing Mechanism
- ◆ Front Light Optional
- ◆ Supports Local Playlist
- ◆ Remote Content Update by HTTP Server, CMS Server or Web

Specifications:

Model:	M13Qxx
Display:	13,3" EPD Monochrome eInk
Display Area:	221 x 269 mm
Resolution:	1200 x 1600
Color:	16 Gray Level (monochrome)
Contrast Ratio:	12:01
% Reflectance:	40
Front Light:	LCS-M13Q4x: with Front Light LCS-M13Q3x: without Front Light
Flash Size:	eMMC 8G
RAM:	DDR 2 LP 512MB
Key:	Power on/off (on back) / Reset Hole (on back)
G Sensor:	Portrait Mode & Landscape Mode
Connectors:	Micro USB 2.0 / SD Card Slot / Mini SIM / DC / Ethernet RJ45 (optional)
LED indicator:	Blue blinking on Backside for Power On
Connectivity:	LCS-M13Qx6: 4G LTE, LAN LCS-M13Qx7: BT4.1 / Wi-Fi 802.11b/g/n, LAN
OS:	Android 4.4.2
Power Consumption:	Static Page: 0mA / 0V Standby: 300mA / 12V (depending on configuration, TBD) Page Change: 600mA / 12V (depending on configuration, TBD)
Tempered Glass:	5 mm AR Glass
Outdoor Design:	Compatible with IP66 & IK07
Bezel Width:	22 / 22 / 22 / 22 mm (Left/Right/Top/Bottom)
Dimension (L x W x H):	365,4 x 290,6 x 48,9 mm
Operation Temp.:	0°C~50°C (4bit image), -15°C~0°C (1bit image), 50°C~65°C (1bit image)